


**CONNECTORS**  
**J1:** LINE INPUT CONNECTOR, MOLEX BEAU 71803-C SCREW TERMINAL, MAX TORQUE 1.3Nm.  
**J2, J3:** GLOBAL OPTIONS MATING CONNECTOR: MOLEX 50-37-5043 PIN 08-70-1040.  
**J4:** OUTPUT POWER CONNECTOR MODULES 1,2,3,4,5,6: BEAU TERMINAL CONNECTOR: #6-32 SCREW TERMINALS. MODULE 7: M6 BY 10mm THREADED STUD

**ACCESSORIES**  
 61069 PARALLEL LINKS  
 61070 SERIES LINKS  
 362D010 'U' LINK  
 61070  
 61069  
 362D010

**NOTES**  
 ALL DIMENSIONS mm (INCHES)  
 MOUNTING HOLES (M4) ON BASE AND SIDE  
 MAX SCREW PENETRATION IS 4mm  
 RECOMMENDED TORQUE ON SCREWS IS 2Nm  
 WEIGHT IS 2.5KG

TOLERANCES UNLESS OTHERWISE STATED,  
 ACCORDING TO DIN 2768-1/-2 CLASS m  
 ALL DIMENSIONS IN mm.



**MATERIAL**  
 61153  
**FINISH**  
 SCALE: NOT TO SCALE

**DOCUMENT NO.** 61153  
**TITLE** 3GEN 4SLOT MECHANICAL DRAWING  
**PREPARED** M.P. 15-08-00  
**CHECKED** S.D. 16-08-00

**TITLE (SHORT FORM)**  
**RELEASED** P.F. 16-08-00

**EXCELSYS TECHNOLOGIES LTD.**  
 SWORDS BUSINESS PARK,  
 SWORDS CO DUBLIN, IRELAND.  
 (T) +353 1 8900933 (F) +353 1 8901358  
 (WEB) www.excelsys.com  
 PAGE 1 OF 1

REV	ECN #	SIGNED	DATE
02	E0147	A.CUNN.	16-01-02
01		M.P.	27-07-00
00		M.P.	15-08-00